

ProDockStation®

Universal Dual Display Docking Station



Expand the Capabilities of Windows, Mac and Chrome Devices and Connect to up to 3 Displays



Simple, Effective Universal Connectivity

Enjoy universal compatibility with a wide range of operating systems, the ProDockStation® provides a simple and effective connectivity solution for charging, data transfer and video display from USB-C and USB-A devices.

Display, Charge, and Transfer with Ease

With plug and play technology, connecting to the ProDockStation is fast and convenient. Simply connect devices with one of the included cables to transfer audio, video, data and power from a single computer port.

Connect up to Three 4K Displays Simultaneously

Whether working with demanding applications, multitasking, or watching videos and films, the ProDockStation allows you to enjoy crisp 4K resolution across up to three monitors with Windows and MAC (including M1 and M1X) devices.

Features:

- ✓ USB-C and USB-A Compatible
- ✓ Supports up to 3 External Monitors
- ✓ 2 x DisplayPort
- ✓ 3 x HDMI
- ✓ 2 x USB-C
- ✓ 3 x USB-A
- ✓ Gigabit Ethernet
- ✓ 3.5mm Audio
- ✓ 100W Power
- ✓ Windows, Apple OS (including M1, M1X), and Chrome OS Compatible
- ✓ 0.5m USB-C to USB-A and USB-C to USB-C Cables Included
- ✓ Kensington® Security Slot
- ✓ Power Button

Part Code: HYP-USBCAPD-S





- | | |
|-----------------------------------|---|
| 1 USB-C Interface | 7 DC 24V |
| 2 USB-A (10Gbps) Charging | 8 Gigabit Ethernet |
| 3 USB-C (10Gbps) Charging | 9 2 x USB-A 3.0 (5Gbps) |
| 4 USB-C (5Gbps) Data | 10 2x DisplayPort 1.2
2x HDMI 2.0 |
| 5 Headset/ Mic 3.5mm | 11 HDMI DP ALT MODE |
| 6 Kensington Security Slot | |

Specification

Product Size: 191 (L) x 85 (W)x 31.8 (H) mm

Box Size: 280 (L) x 210 (W)x 42 (H) mm

Weight: 850g (including 130 DC power adapter, USB-C to C cable and USB-A to C cable).

Material: Plastic housing covered by soft silicon sheet.

Interface Specification

Support extended screens on both Mac OS (Intel and M1 chip) and Windows

HDMI 1 (Display Link) Single, Dual or Triple Display Resolution: 3840*2160@60Hz. Audio: Stereo. Audio Sample Rate: 16bit/48K

DisplayPort 1 (Display Link) Single, Dual or Triple Display Resolution: 3840*2160@60Hz. Audio: Stereo. Audio Sample Rate: 16bit/48K

HDMI 2 (Display Link) Single, Dual or Triple Display Resolution: 3840*2160@60Hz. Audio: Stereo. Audio Sample Rate: 16bit/48K

DisplayPort 2 (Display Link) Single, Dual or Triple Display Resolution: 3840*2160@60Hz. Audio: Stereo. Audio Sample Rate: 16bit/48K

HDMI 3(DP ALT mode) Single, Dual or Triple Display Resolution: 3840*2160@30Hz. Audio: 7.1 channel. Audio Sample Rate: 24bit/192K.

DC Power: 130W. Input: 24V/5.42. Charge PC: 100W.

Operating Systems: Apple OS (including M1, M1X), Windows, Chrome OS

Certification: RoHS, REACH, Prop65, CE FCC